Safety Data Sheet- Portland Cement (Type IL)

Continental Cement Company, L.L.C. 10107 Hwy 79 South Hannibal, MO 63401 Phone: 573.221.1740 Fax: 573.221.8487

Safety Data Sheet For Portland Cement (Type IL)



Section 1 – Product and Company Information 1.1 Product Identifier Identify: Portland Limestone Cement "PLC" (Type IL) Synonyms: Portland Cement, Portland Limestone Cement (PLC) 1.2 Identified Use Use: Acts as a binding agent in concrete and mortar work. Manufacturer Name: Continental Cement Transportation Emergency Telephone #'s: Address: 10107 HWY 79 South Hannibal, MO 63401 Night Time: 573.221.1740

Telephone # for Information: 573.221.1740 Last Updated: 01/13/2023 Website: www.continentalcement.com

Section 2 – Hazardous Identification

2.1- Classification of the Substance or Material

GHS-US Classification-(Category) Acute Toxicity Oral: 4 Acute Toxicity Dermal: 4 Skin Corrosion/Irritation: 1B Eye Damage: 1 Respiratory Sensitization: 1 Skin Sensitization: Category 1 Carcinogenicity: 1A Specific Target Organ Toxicity: 3



SDS for Portland Cement (Type IL)

Signal Word: Danger

Hazard Statements

H302: Harmful if Swallowed

H312: Harmful in Contact With Skin

H314: Causes Severe Skin Burns and Eye Damage

H318: Causes Serious Eye Damage

H335: May Cause Allergy or Asthma Symptoms or Breathing Difficulties if Inhaled

H317: May cause an Allergic Reaction

H350: May Cause Cancer

Precautionary Statements

Prevention Statements

- P201: Obtain special instructions before use
- P202: Do not handle until all safety precautions have been read and understood
- P260: Do not breathe dusts
- P261: Avoid breathing dust/fume/gas/mist/vapors/sprays
- P264: Wash thoroughly after handling
- P270: Do not eat, drink, or smoke when using this product
- P280: Wear protective gloves, protective clothing, eye protection, face protection
- P361: Remove contaminated clothing and wash before reuse
- P271: Use outdoors or in a well-ventilated area
- P284: In case of inadequate ventilation: Use Respiratory Protection

Response Statements

P301 + P330 + P331: If Swallowed: Rinse Mouth. Do NOT induce vomiting. Immediately call a poison center/physician.

P302 + P352: If on Skin: Wash with plenty of soap and water.

P303 + P353 + P361: If on Skin (or Hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. Contact a poison center/physician if needed.

P304 + P340 + P312: If Inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P305 + P310 + P351 + P338: If in Eyes: Rinses cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue Rinsing. Immediately call a poison center/doctor.

P308 + P313: If exposed or concerned: get medical advice/attention.

P313 + P332: If skin irritation occurs: get medical advice/attention.

P362: Take off contaminated clothing and wash before reuse.

Storage Statements

P403 + P233: Store in a well-ventilated place. Store in an appropriate container or containment.

P405: Store locked up.

Disposal Statements

• Dispose of contents and containers in accordance with local, state, and federal Regulations.

CAS #	Component	Percent (Range)
65997-15-1	Cement, Portland, Chemicals	90 – 95
13397-24-5	Gypsum (Calcium sulfate)	6-8
1317-65-3	Limestone (Calcium carbonate)	0-15
14808-60-7	Quartz	0 - 0.1

S_{1}	Section 3	- Com	position/Infor	mation on	Ingredients
---------	-----------	-------	----------------	-----------	-------------

Other Components: Cement is made from materials mined from the earth and processed using energy provided by fuels. Additional materials, such as fly ash, kiln dust and slag may also be introduced into the cement manufacturing process. A chemical analysis of cement may reveal trace amounts of naturally occurring but potentially harmful chemical compounds such as free crystalline silica, organic compounds, potassium and sodium compounds, heavy metals including cadmium, chromium (including hexavalent chromium), nickel and lead. Other trace constituents may include calcium oxide (also known as free lime or quick lime) and organic compounds from grinding aids such as amine acetate salts, glycols and 1,2-ethanediol.

Section 4 – First Aid Measures

4.1 First Aid:

General Advice: Move out of hazardous environment. Seek medical attention as needed. Obtain SDS for informational purposes.

First-aid measures after eye contact: Rinse eyes immediately with water. Continue rinsing for several minutes (15 minutes or greater) to ensure particle removal. Get medical consultation immediately.

First-aid measures after skin contact: Flush skin with water immediately for 15 minutes. Wash skin with mild soap. Remove contaminated clothing. Seek medical attention immediately.

First-aid measures after ingestion: Do not induce vomiting. Contact poison center/physician immediately.

First-aid measures after inhalation: Remove victim to fresh air. Contact medical personnel immediately.

4.2 Important Symptoms or Effects Inhalation: Difficulty Breathing, Respiratory Irritation Skin Contact: Burns, Pain, Blisters Eye Contact: Burn, Pain, Discomfort, Severe Eye Damage Ingestion: Nausea, Vomiting

Section 5 – Firefighting Measures

Extinguishing Equipment: Suitable media to extinguish surrounding environment.
Hazardous Combustion Products: None
Fire Hazard: Product does not burn.
Hazardous Decomposition or Byproducts: None spontaneously.
Firefighting Instructions: Wear appropriate firefighting equipment.

Section 6 – Accidental Release Measures

General Measures: Use personal protective equipment outlined in Section 8.

Containment: Stop the spill in a safe manner. Create barricade to contain.

Clean-Up: Collect the material and place in approved containers. Ensure that dust generation is down to a minimum due to the hazards of the dust.

Environmental: Ensure product is quickly swept up to ensure cement does not go into sewers, ditches, drains or waterways.

Section 7 – Handling and Storage

Handling Procedures:

Avoid skin and eye contact with the material or breathing the dust. Wear appropriate personal protective equipment as described in Section 8. Wash thoroughly after exposure to product. Product is an engulfment hazard if stored in large enough container.

Storage Procedures:

Store in a cool, dry environment where only authorized personnel has access to.

Precautions to Be Taken for Handling and Storing:

Protect against physical damage. Store the material in a cool, dry well-ventilated location.

Incompatible Materials:

Water/moisture exposure will cause material to generate heat. Keep away from strong acids and oxidizers.

Section 8 – Exposure Control/Personal Protection

Control Parameters:

Exposure Limits for Individual Components

(T=Total Respirable, R=Respirable fraction, I=Inhalable-aerosol)

Component	OSHA PEL	ACGIH TLV	NIOSH REL
Portland Cement	15 mg/m3 (T);	1 mg/m3 (R)	10 mg/m3 (T);
	5 mg/m3 (R)	<1% Crystalline silica	5 mg/m3 (R)
Limestone (Calcium carbonate)	15 mg/m3 (T);	10 mg/m3	10 mg/m3 (T);
	5 mg/m3 (R)		5 mg/m3 (R)
Calcium oxide	5 mg/m3	2 mg/m3	2 mg/m3
Silica dioxide (Amorphous)	80 mg/m3 / (% SiO2)	None	6 mg/m3
Crystalline Silica (Quartz)	10 mg/m3 (R) /(% SiO2 + 2)	0.025 mg/m3 (R)	0.05 mg/m3 (R)
	30 mg/m3 (T) /(% SiO2 + 2)		
Gypsum (Calcium Sulfate)	15 mg/m3 (T);	10 mg/m3 (T)	10 mg/m3 (T);
	5 mg/m3 (R)		5 mg/m3 (R)

Safety Data Sheet- Portland Cement (Type IL)

Sulfur trioxide	1 mg/m3 (as H2SO4)	0.2 mg/m3 (as H2SO4)	1 mg/m3 (as H2SO4)
Aluminum Oxide	15 mg/m3 (T)	1 mg/m3 (R) (as Al metal	Not established
	5 mg/m3 (R) (as Al)	& insoluble compounds)	
Iron Oxide	10 mg/m3 (as fume)	5 mg/m3 (R)	5 mg/m3 (dust/fume
			as Fe)
Magnesium oxide	15 mg/m3	10 mg/m3 (I)	Not established
Slags, ferrous metals, blast	15 mg/m3 (T);	10 mg/m3 (T);	Not established
furnace	5 mg/m3 (R)	3 mg/m3 (R)	

Exposure Controls:

Engineering:

Provide exhaust or local ventilation or other engineering controls to keep the airborne concentrations of dust below their respective threshold limit value if needed.

Respiratory Protection (Specify Type):

Use local/general ventilation if possible. In situations with poor ventilation, use a NIOSH approved respirator or dust mask to protect against the inhalation of dust.

Protective Gloves:

Suitable gloves with wrist/arm cuffs should be worn to protect avoid direct contact with the skin.

Eye Protection:

Use chemical safety glasses/goggles and/or a full face shield. Avoid wearing contact lens when using this product.

Other Protective Clothing or Equipment:

Wear impervious protective clothing, including boots, gloves, and coveralls, as appropriate, to prevent skin contact. Structural firefighter's protective clothing will only provide limited protection.

Section 9 – Physical and Chemical Properties

Appearance: Solid, grey to white powder Upper Flammability: No data available Lower Flammability: No data available Odor: No observable odor Vapor Pressure: No data available Vapor Density: No data available pH: 12-14 (in water) Relative Density: No data available Melting Point: No data available Freezing Point: No data available Solubility: Slight Initial Boiling point: No data available Boiling Range: No data available Flash Point: No data available Evaporation Rate: No data available Flammability: Not flammable Vapor Pressure: No data available SDS for Portland Cement (Type IL)

Vapor Density: No data available Relative Density: No data available Solubility: No data available Partition Coefficient: No data available Auto Ignition Temperature: No data available Decomposition Temperature: No data available Viscosity: No data available

Section 10 – Stability and Reactivity

10.1 Reactivity

Reacts with water to form calcium hydroxide which can irritate or damage skin and eyes. Do not mix with other chemicals.

10.2: Stability Stable under normal dry storage conditions.

10.3 Conditions to Avoid Strong acids, aluminum metal and oxidizers.

10.4 Incompatible Materials None Known

10.5 Hazardous Decomposition Products None Known

Section 11 – Toxicological information

Portland Cement (65997-15-1) IDLH = 5000 mg/m^3

Quartz (14808-60-7) LD50 oral rat = 500 mg/kg IARC Group = 1 NTP Status = 2

Limestone (1317-65-3) LD50 oral rat = 6450 mg/kg

Calcium Oxide (CAS 1305-78-8) Carcinogenicity: Not identified as a known or suspected carcinogen.

Acute Toxicity: No data available

Skin Corrosion/Irritation: Skin-human Result: severe skin irritation Serious eye damage/irritation: Eyes-Rabbit Result: Serious eye damage is possible

Respiratory/Skin sensitization: No data

Germ Cell Mutagenicity: No data

Reproductive Toxicity: No data Available

Specific target organ toxicity-single exposure: Inhalation-Irritation is possible.

Specific target organ toxicity-repeated exposure: No data

Aspiration hazard: No data available

Routes of Exposure: Skin and eye contact, inhalation, and ingestion.

Specific Target Organ Toxicity (single exposure): Respiratory irritation

Skin corrosion/irritation: Severe burns

Eye Damage/Irritation: Serious eye damage

Respiratory/Skin Irritation: Allergic skin reaction, Respiratory tract irritation

Carcinogenicity: Can cause cancer (Quartz)

Symptoms after contact related to exposure/toxicological characteristics Skin Contact: Burns, irritation, blisters, rash, pain and discomfort. Eye Contact: Burn, eye damage, redness, excessive watering of eye. Ingestion: Nausea, Vomiting. Inhalation: Irritation of the respiratory tract.

Section 12 – Ecological Information

12.1 Toxicity: No information is available.

12.2 Persistence and Degradability: No data Available

12.3 Bio-accumulative potential: No data available

12.4 Mobility in Soil: No data available

12.5 Other Adverse Effects: No data available

Section 13 – Disposal Considerations

13.1 Waste Treatment Methods

Disposal Recommendations: Dispose material in accordance with any applicable local, state, and Federal regulations.

Section 14 – Transportation Information

Proper Shipping Name N/A – not regulated. Hazard Class N/A – not regulated. UN Shipping ID Number N/A – not regulated. Packing Group N/A – not regulated. Environmental/IMDG Codes N/A – not regulated.

Section 15 – Regulatory Information

15.1 US Federal Regulations

Cement, Portland, chemicals (65997-15-1): Listed on US TSCA (Toxic Substance Control Act) Inventory.

Limestone (1317-65-3): Listed on US TSCA (Toxic Substance Control Act) Inventory.

Quartz (14808-60-7): Listed on US TSCA (Toxic Substance Control Act) Inventory.

This product contains one or more chemical components or ingredients that may require identification and/or reporting under SARA Section 302, SARA Section 311/312/313, CERCLA and/or TSCA. An examination of the components of this product should be conducted by a qualified environmental professional to determine if such identification or reporting is required by federal law.

15.2 State Regulations

State or Local Regulations: Product contains quartz or crystalline silica and trace amounts of other chemicals known to the State of California as causing cancer, birth defects, and/or reproductive harm.

Section 16 – Other information

SDS was prepared according to the Hazard Communication Standard (CFR 29 1910.1200). Prepared 01/13/2023.

Abbreviations

- ACGIH American Conference of Governmental Industrial Hygienists
- CAS Chemical Abstract Service
- CERCLA Comprehensive Emergency Response and Comprehensive Liability Act
- CFR Code of Federal Regulations DOT Department of Transportation
- GHS Globally Harmonized System Globally Harmonized System
- IARC International Agency for Research on Cancer
- IMDG International Maritime Dangerous Goods
- NIOSH --- National Institute of Occupational Safety and Health
- NTP National Toxicology Program
- OSHA Occupational Safety and Health Administration
- PEL Permissible Exposure Limit
- REL Recommended Exposure Limit RQ Reportable Quantity
- SARA Superfund Amendments and Reauthorization Act
- SDS Safety Data Sheet
- TLV Threshold Limit Value
- TPQ Threshold Planning Quantity
- TSCA Toxic Substances Control Act
- TWA Time Weighted Average